



# ENERG

енергия · ενεργεια



I - Klima - Kälte - Wärme || OH 1-29e - W/W Art.Nr.: B11208



55 °C

35 °C



**59** dB



--- dB


■ 33  
■ **33**  
■ 33  
kW


■ 38  
■ **38**  
■ 38  
kW




Package (heat pumps and combination heater with heat pump)																																							
Seasonal space heating energy efficiency of heat pump ( $\eta_S$ )								1	161	%																													
Rated output of the heat pump ( $P_{rated}$ kW)									33.00																														
Temperature control		Class		VII	(Table 1)	+	2	3.5	%																														
Supplementary boiler		Package with hot water storage tank		no				$P_{sup}$ kW (rated output of supplementary heater)																															
				$\eta_S$ % (sup)																																			
				$(\eta_S \text{ % (sup)} - 1) \times (\alpha_{WE})$		=	-	3	%																														
				$(\alpha_{WE})$																																			
Solar contribution				$(A_{Koll} \text{ m}^2)$				$(\eta_{Koll} \text{ %})$																															
				$(V_{Sp} \text{ m}^3)$				(standstill heat loss of the storage tank in W)																															
								$(\eta_{Sp})$																															
				$((294/(P_{rated} \times 11)) \times (A_{Koll} \text{ m}^2) + (115/(P_{rated} \times 11)) \times (V_{Sp} \text{ m}^3)) \times 0.45 \times ((\eta_{Koll} \text{ %}) / 100) \times (\eta_{Sp})$			=	+	4	%																													
Seasonal space heating energy efficiency of package under average climate								5	165	%																													
									rounded to the nearest integer																														
Seasonal space heating energy efficiency class of package under average climate																																							
<table border="1"> <tr> <td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>X</td> </tr> <tr> <td><b>G</b></td><td><b>F</b></td><td><b>E</b></td><td><b>D</b></td><td><b>C</b></td><td><b>B</b></td><td><b>A</b></td><td><b>A+</b></td><td><b>A++</b></td><td><b>A+++</b></td> </tr> <tr> <td>&lt; 30 %</td><td>≥ 30 %</td><td>≥ 34 %</td><td>≥ 36 %</td><td>≥ 75 %</td><td>≥ 82 %</td><td>≥ 90 %</td><td>≥ 98 %</td><td>≥ 125 %</td><td>≥ 150 %</td> </tr> </table>																			X	<b>G</b>	<b>F</b>	<b>E</b>	<b>D</b>	<b>C</b>	<b>B</b>	<b>A</b>	<b>A+</b>	<b>A++</b>	<b>A+++</b>	< 30 %	≥ 30 %	≥ 34 %	≥ 36 %	≥ 75 %	≥ 82 %	≥ 90 %	≥ 98 %	≥ 125 %	≥ 150 %
									X																														
<b>G</b>	<b>F</b>	<b>E</b>	<b>D</b>	<b>C</b>	<b>B</b>	<b>A</b>	<b>A+</b>	<b>A++</b>	<b>A+++</b>																														
< 30 %	≥ 30 %	≥ 34 %	≥ 36 %	≥ 75 %	≥ 82 %	≥ 90 %	≥ 98 %	≥ 125 %	≥ 150 %																														
Seasonal space heating energy efficiency under colder and warmer climate conditions																																							
colder	163	%		colder	5	165	-V	-2	=	167	%																												
warmer	162	%		warmer	5	165	+VI	1	=	166	%																												

The energy efficiency of the package of products provided for in this fiche may not correspond to its actual energy efficiency once installed in a building, as the efficiency is influenced by further factors such as heat loss in the distribution system and the dimensioning of the products in relation to building size and characteristics.

<b>Product fiche</b>		 <b>AC Cooling Heating</b>		
<b>Manufacturer</b>	CTA AG			
<b>Model</b>	OH 1-29e W/W			
<b>Information on energy efficiency class and rated output</b>				
	Average / Low temperature	Average / Medium temperature		
Space heating energy efficiency class	A++	A++	-	
Rated heat output	37.20	33.00	kW	
Seasonal space heating energy efficiency	233	161	%	
Annual final energy consumption space heating	12698	16132	kWh	
Sound power level indoors		59	dB	
<b>Special precautions during assembly, installation or maintenance</b>				
see installation and maintenance instructions				
<b>Additional information</b>				
	Low temperature	Medium temperature		
Rated heat output colder climate	37.20	33.00	kW	
Rated heat output warmer climate	37.20	33.00	kW	
Seasonal space heating energy efficiency colder climate	238	163	%	
Seasonal space heating energy efficiency warmer climate	237	162	%	
Annual final energy consumption colder climate	14916	19004	kWh	
Annual final energy consumption warmer climate	8086	10367	kWh	
Sound power level outdoors		-	dB	
<b>Technical data of the temperature controller</b>				
<b>Manufacturer</b>	Siemens			
<b>Model</b>	RVS 61			
Class of the controller		VII	-	
Contribution of the controller to seasonal space heating energy efficiency		3.5	%	
<b>Contact</b>	CTA AG, Hunzigenstrasse 2, CH-3110 Münsingen			

<b>Model</b>				<b>OH 1-29e W/W</b>						
Brine-to-water heat pump: (Yes/No)				No						
Water-to-water heat pump: (Yes/No)				Yes						
Air-to-water heat pump: (Yes/No)				No						
Low temperature heat pump: (Yes/No)				No						
Equipped with supplementary heater: (Yes/No)				No						
Heat pump combination heater: (Yes/No)				No						
Application: (Low temperature/Medium temperature)				Medium temperature						
Climate: (Colder/Average/Warmer)				Average						
<b>Item</b>	<b>Symbol</b>	<b>Value</b>	<b>Unit</b>	<b>Item</b>	<b>Symbol</b>	<b>Value</b>	<b>Unit</b>			
<b>Rated heat output</b>	Prated	33.00	kW	<b>Seasonal space heating energy efficiency</b>	$\eta_S$	161	%			
<b>Declared capacity for heating for part load at indoor temperature 20°C and outdoor temperature Tj</b>				<b>Declared coefficient of performance for part load at indoor temperature 20°C and outdoor temperature Tj</b>						
Tj = -7°C	Pdh	33.50	kW	Tj = -7°C	COPd	3.70	-			
Tj = +2°C	Pdh	35.50	kW	Tj = +2°C	COPd	4.72	-			
Tj = +7°C	Pdh	37.00	kW	Tj = +7°C	COPd	5.61	-			
Tj = +12°C	Pdh	38.40	kW	Tj = +12°C	COPd	6.79	-			
Tj = biv	Pdh	33.00	kW	Tj = biv	COPd	3.46	-			
Tj = TOL	Pdh	33.00	kW	Tj = TOL	COPd	3.46	-			
Tj = -15°C (if TOL < -20°C)	Pdh	-	kW	Tj = -15°C if TOL < -20°C)	COPd	-	-			
Bivalent temperature	T <sub>biv</sub>	-10	°C	Operation limit temperature	TOL	-10	°C			
Cycling interval capacity for heating	P <sub>psych</sub>	-	kW	Cycling interval efficiency	COP <sub>psych</sub>	-	-			
Degradation co-efficient	Cdh	0.9	-	Heating water operating limit temperature	WTOL	63	°C			
<b>Power consumption in modes other than active mode</b>				<b>Supplementary heater</b>						
Off mode	P <sub>OFF</sub>	0.003	kW	Rated heat output	P <sub>sup</sub>	-	kW			
Thermostat-off mode	P <sub>TO</sub>	0.012	kW	Type of energy input	-					
Standby mode	P <sub>SB</sub>	0.003	kW							
Crankcase heater mode	P <sub>CK</sub>	0.003	kW							
<b>Other items</b>										
Capacity control	fixed			Rated air flow rate, outdoors	-	-	m <sup>3</sup> /h			
Sound power level, indoors/outdoors	L <sub>WA</sub>	59 / -	dB	Rated brine or water flow rate, outdoor heat exchanger	-	7.7	m <sup>3</sup> /h			
Emissions of nitrogen oxides	NO <sub>x</sub>	-	mg/kWh							
<b>For heat pump combination heater</b>										
Declared load profile	-			Water heating energy efficiency	$\eta_{wh}$	-	%			
Daily electricity consumption	Q <sub>elec</sub>	-	kWh	Daily fuel consumption	Q <sub>fuel</sub>	-	kWh			
<b>Contact</b>	CTA AG, Hunzigenstrasse 2, CH-3110 Münsingen									

<b>Model</b>				<b>OH 1-29e W/W</b>						
Brine-to-water heat pump: (Yes/No)				No						
Water-to-water heat pump: (Yes/No)				Yes						
Air-to-water heat pump: (Yes/No)				No						
Low temperature heat pump: (Yes/No)				No						
Equipped with supplementary heater: (Yes/No)				No						
Heat pump combination heater: (Yes/No)				No						
Application: (Low temperature/Medium temperature)				Low temperature						
Climate: (Colder/Average/Warmer)				Average						
<b>Item</b>	<b>Symbol</b>	<b>Value</b>	<b>Unit</b>	<b>Item</b>	<b>Symbol</b>	<b>Value</b>	<b>Unit</b>			
<b>Rated heat output</b>	Prated	37.20	kW	<b>Seasonal space heating energy efficiency</b>	$\eta_S$	233	%			
<b>Declared capacity for heating for part load at indoor temperature 20°C and outdoor temperature Tj</b>				<b>Declared coefficient of performance for part load at indoor temperature 20°C and outdoor temperature Tj</b>						
Tj = -7°C	Pdh	37.40	kW	Tj = -7°C	COPd	5.97	-			
Tj = +2°C	Pdh	38.40	kW	Tj = +2°C	COPd	6.79	-			
Tj = +7°C	Pdh	39.20	kW	Tj = +7°C	COPd	7.54	-			
Tj = +12°C	Pdh	39.70	kW	Tj = +12°C	COPd	8.12	-			
Tj = biv	Pdh	37.20	kW	Tj = biv	COPd	5.79	-			
Tj = TOL	Pdh	37.20	kW	Tj = TOL	COPd	5.79	-			
Tj = -15°C (if TOL < -20°C)	Pdh	-	kW	Tj = -15°C if TOL < -20°C)	COPd	-	-			
Bivalent temperature	T <sub>biv</sub>	-10	°C	Operation limit temperature	TOL	-10	°C			
Cycling interval capacity for heating	P <sub>psych</sub>	-	kW	Cycling interval efficiency	COP <sub>psych</sub>	-	-			
Degradation co-efficient	Cdh	0.9	-	Heating water operating limit temperature	WTOL	63	°C			
<b>Power consumption in modes other than active mode</b>				<b>Supplementary heater</b>						
Off mode	P <sub>OFF</sub>	0.003	kW	Rated heat output	P <sub>sup</sub>	-	kW			
Thermostat-off mode	P <sub>TO</sub>	0.012	kW	Type of energy input	-					
Standby mode	P <sub>SB</sub>	0.003	kW							
Crankcase heater mode	P <sub>CK</sub>	0.003	kW							
<b>Other items</b>										
Capacity control	fixed			Rated air flow rate, outdoors	-	-	m <sup>3</sup> /h			
Sound power level, indoors/outdoors	L <sub>WA</sub>	59 / -	dB	Rated brine or water flow rate, outdoor heat exchanger	-	7.7	m <sup>3</sup> /h			
Emissions of nitrogen oxides	NO <sub>x</sub>	-	mg/kWh							
<b>For heat pump combination heater</b>										
Declared load profile	-			Water heating energy efficiency	$\eta_{wh}$	-	%			
Daily electricity consumption	Q <sub>elec</sub>	-	kWh	Daily fuel consumption	Q <sub>fuel</sub>	-	kWh			
<b>Contact</b>	CTA AG, Hunzigenstrasse 2, CH-3110 Münsingen									